

▼ Specialist PA Ceiling Speakers

Fast-Fix 5W 100V 100mm (4") Twin Cone

Includes transformer cover, cable restraint, 4 way terminal and 22µF line monitoring capacitor for use in EWIS systems.

Speaker driver:	C 2101C
Power taps:	0.33, 0.66, 1.25, 2.5, 5W
SPL 1W @ 1m	90dB @ 1kHz ±2dB
Freq response:	100Hz - 15kHz
Terminal type:	4 way screw terminal block & 22µF bipolar capacitor
Ceiling cutout:	150mm Ø
Mounting depth:	111mm
Grille	Aluminium



5 Year Warranty

Price Each	RRP	4+	10+
C 2122C White	51.95	48.95	45.50

Fast-Fix 15W 100V 100mm (4") IP55 Bathroom Speaker

This IP55 rated bathroom speaker, employs a 100mm high performance driver, constructed from an all-weather polypropylene cone and rubber surround. Fitted with a high quality 100V line matching transformer tapped at 2.5, 5, 10 & 15W. Installation is simplified by the use of a 'flip-lock' mounting system. Rust free aluminium grille, ideal for bathrooms or tropical environments.

Power taps:	2.5, 5, 10, 15W
Terminal type:	4 way screw terminal block & 22µF bipolar capacitor
Freq. response:	70Hz - 12kHz
SPL 1W@1m:	87dB
Dimensions (mm):	167Ø x 125H
Cutout size (mm):	140Ø



5 Year Warranty

Price Each	RRP	4+	12+
C 2097	79.50	74.75	69.25

Redback® Vandal Resistant Coaxial Ceiling Speaker

Designed to withstand the physical abuse of vandals. Access to the 130mm coaxial speaker requires a security torx tool, minimising unauthorised tampering and/or theft. Suitable for use in prisons, train stations, bus stations, malls, etc. Adjustable bracket suits ceiling thickness 4-35mm. Fitted with 4 way terminal block & 22µF bipolar capacitor.

Power taps:	1.25, 2.5, 5, 10W
Freq. response:	80Hz - 20kHz
SPL 1W@1m:	91dB
Dimensions (mm):	189Ø x 110H
Cutout size (mm):	155Ø



5 Year Warranty

Price Each	RRP	2+	4+
C 0887	125.00	115.00	100.00

130mm 100V Vandal Resistant EWIS Ceiling Speaker

EN54-24:2008 & BS5839:8 compliant.

This 130mm (5") 10W ceiling speaker is engineered to EN54-24 and provides high levels of speech intelligibility for EWIS evacuation communication systems. The housing provides a high degree of protection from moisture, dust and vandalism. Installation is via the spring loaded steel torsion plates on the sides of the fire rated rear speaker enclosure. Cabling can be terminated using the 3 way ceramic terminal block.



5 Year Warranty

Active EQ required:	No	Mounting depth:	110mm
Power taps:	1.25, 2.5, 5, 10W	Terminal type:	2 way screw terminal & 22µF bipolar capacitor
SPL 1W @ 1m:	90dB @ average 100-10kHz		
Freq response:	130Hz - 18.5kHz		
Ceiling cutout:	164mm Ø		
Price Each	RRP	2+	4+
CF0887 White	165.00	150.00	132.00

150mm (6") 100V Marine Ceiling Speaker

This compact, low profile speaker features a 150mm (6") 6W driver and snap fit edge to edge aluminium grille for a stylish finish. Though suitable for any 100V line general PA usage, it has been designed to be ideally used in large passenger ferries and commercial vessels. It features sealed cable gland entries, rear dust cover and dual spring retention clips - plus additional screw securing holes in case of rough seas! Termination is made easy with a pluggable 4 pin terminal block for loop in, loop out cabling. A thermal fuse is also fitted to protect the speaker line.



NEW

5 Year Warranty

EASE DATA AVAILABLE.

Power taps:	0.375, 0.75, 1.15, 3, 6W	Terminal type:	4 way pluggable terminal block
SPL 1W @ 1m	91dB @ 1kHz ±2dB	Flame retardant cover:	Yes
Freq response:	100Hz - 15kHz	Cable entry:	PG13.5 (10-12mm OD cable)
Ceiling cutout:	165mm Ø		
Mounting depth:	73mm		

Price Each	RRP	6+	12+
CM2111 White	129.00	119.00	115.00

165mm (6.5") Active PA Speaker With Dante®

This 6.5" PA ceiling speaker offers Dante connectivity for zone audio over IP networks. It can be powered directly from a PoE switch and offers excellent audio performance for PA, BGM and paging purposes. Dante transmits 24-bit audio (44.1K/48KHz) with full signal control over standard ethernet cabling.



NEW

Connection:	RJ45
Power rating:	15 Watts
SPL 1W @ 1m	91dB
Freq response:	80Hz - 18kHz
Mounting depth:	130mm
Ceiling cutout:	175mm

Price Each	RRP	4+	10+
CD2193A	599.00	569.00	539.00

▼ Holesaws For Ceiling Speakers

Holesaws

High speed holesaws for cutting precise neat holes into plasterboard, plywood & acrylic sheet (not recommended for cutting metal). Suitable for power drills with a standard 3/8" chuck. T 2312A Cuts hole for One-Shot® 100mm speaker & grill combinations. For 200mm speakers, use the T 2314A adjustable model.

Price Each	RRP	2+	4+
T 2312A 140mm holesaw including arbor	105.00	96.75	85.25
T 2314A Adjustable holesaw 40mm - 300mm	200.00	179.00	160.00
T 2313A Spare cutter for T 2312A	63.25	57.50	54.75
T 2315B Spare tungsten cutting blades for T 2314A (pr)	26.50	24.95	22.25