

ANBI Switch Battery Isolator



Installs in just 15 minutes and protects your seldom used vehicle from damaging battery drain.

The ANBI switch is designed to avoid the inconvenience of having a completely flat battery. The switch eliminates drainage of stored power by isolating the battery from components. Even when your ignition key is off, there are still components that draw current and continue to drain your battery. This is a common cause of vehicles not starting after a period of inactivity.

Features • Australian designed • Isolates negative terminal to prevent power drain • Ideal for boats, cars, jet skis, golf carts, caravans - anything with an automotive battery in it! • Simple installation • Anti-corrosive design • Great theft deterrent

Price Each	RRP
N 2090	49.50
N 2091 Extension lead	24.50
N 2092 Small terminal adaptor kit	19.95
Vehicle specific ANBI Switches	
N 2120 Motorcycle	39.00
N 2121 Ride On Mower	39.00
N 2123 Caravan/Camper	39.00
N 2124 Jet Ski	39.00

Smart 12V Dual Battery Isolator (VSR)



This voltage sensitive relay module is designed to combine two batteries when charging and isolates each when not charging. It essentially isolates your auxiliary battery from your starter battery to prevent you inadvertently fully discharging it. Once the voltage of your starter battery rises above 13.3V the isolator engages to charge both batteries in parallel. When the voltage of the starter battery drops below 12.8V the isolator disengages sending charge solely to the starter battery. Size: 69x69x58mm.

Features • 'Batteries combined' LED indicator • Glass fibre reinforced nylon enclosure • Encapsulated for water & dust protection • No voltage drop

Price Each	RRP	2+	4+
S 2680	59.95	53.95	47.95

Kemo® Low Battery Cut Off Module (12V)



This battery saver protects your 12V car battery from discharge by disconnecting loads to prevent voltage dropping below a preset limit (10.4 to 13.3V). The module automatically reconnects the loads once the battery recharges, typically 0.8V above cut-off limit.

Price Each	RRP
A 0712	52.95

▼ Battery Monitoring

Panel Mount Dual Battery Voltmeter

Dual main/aux voltmeters for monitoring batteries. Measures 6-30V DC. 29mm mounting hole. 19mm thread length.



Price Each	RRP	2+	4+
P 0692	29.95	26.95	23.95

Panel Mount Volt Meter With Graph

Measures 5-30V DC with dial graph and central voltage reading. 29mm mounting hole. 52mm thread length.



Price Each	RRP	4+	10+
P 0693A	19.95	18.50	16.50

Panel Mount Volt & Ammeter

Measures 6-30V DC @ 10A max with internal shunt. 29mm mounting hole. 19mm thread length.



Price Each	RRP	2+	4+
P 0671A	29.95	26.95	23.95

Panel Mount Volt Meter & Thermometer

Includes temperature sensor with 6.3mm spade connection. Measures 6-30V DC. 29mm mounting hole. 19mm thread length. -10°C to 100°C.



Price Each	RRP	2+	4+
P 0699A	17.95	15.95	14.50

Panel Mount Dual Battery Voltmeter

Standard cantura switch style panel meter suitable for the installation and use of all 12-24V vehicles, such as cars, motorcycles, buses, boats, RV's etc. Cutout: 22.5 x 37.5mm.



Price Each	RRP	2+	4+
PA0692 4.2A	29.95	26.95	23.95

Panel Mount Volt Meter

Features a measuring range of 5-32V DC and a working voltage of 12-24V DC. 27Ømm mounting hole. Only 6.35mm deep.



Price Each	RRP	4+	10+
P 0672A	15.95	14.35	12.75

Multi-Function Digital 200A Power Meter




A comprehensive power monitor panel for solar and remote power systems. It displays discharge current, discharge power, discharge impedance, internal resistance, capacity, dump energy, energy consumption and running time. Supplied with a 200A external shunt for easy connection to the system battery.

Cut out dimensions: 87 x 47mm.

Overall dimensions: 89.5 x 49.5 x 25mm.

Price Each	RRP	4+	6+
Q 0592	49.95	44.95	39.95

Flush Mount Power Monitor Panel



A complete power monitoring panel with voltage, current, power and energy consumption (Wh) displayed simultaneously. Easy press fit mount with voltage alarm function. 2000W max. 6.5-100V DC. Available with 20A internal load shunt or 100A external shunt. Cut out dimensions 84.5W x 44.5Hmm.

Overall dimensions: 89.5 x 49.5 x 25mm.

Price Each	RRP	4+	6+
Q 0589 20A	29.95	26.95	23.95
Q 0591 100A (ext. shunt)	39.95	35.95	31.95

Flush Mount Battery Capacity Meter



An adjustable battery capacity readout allowing you to display approximate battery levels for any battery between 1V and 100V. You can set an operation voltage range and the display will show battery capacity in a 5 segment display & percentage reading. 0.1V resolution with 1% accuracy. Cut out dimensions: 87 x 47mm. Overall dimensions: 89.5 x 49.5 x 25mm.

Price Each	RRP	4+	6+
Q 0587	29.95	26.95	23.95

Need help?

Email us any time for assistance.
customerservice@altronics.com.au

Important Note For Wholesale Customers

All prices listed in this catalogue are RRP "retail" prices. To access our competitive wholesale pricing scheme apply for an account via www.altronics.com.au or phone the wholesale division in your state - see back cover for phone numbers.