

▼ Capacitors

Lelon® Electrolytic Capacitors (85°C Rated)



- Low impedance
- Case sizes are smaller than conventional general purpose capacitors, with very high performance.
- Can sizes larger than 8mm diameter have safety vents or rubber bung.
- Temp range -40° to +85°C
- Tolerance: ±20%
- Rated life: 2000-3000hrs
- **All quantities supplied loose.**

Price Each	Value	Volts DC	Surge DC	Ripple (mA)	Diameter	Pitch	Height	RRP	10+	100+
R 5028	2.2µF	63V	79V	28	5	2	11	0.30	0.25	0.15
R 5038	3.3µF	63V	79V	34	5	2	11	0.30	0.25	0.15
R 5084	22µF	25V	32V	75	5	2	11	0.30	0.25	0.15
R 5087	22µF	50V	63V	95	5	2	11	0.35	0.30	0.20
R 5088	22µF	63V	79V	115	6.3	2.5	11	0.95	0.75	0.45
R 5094	33µF	25V	32V	97	5	2	11	0.40	0.35	0.20
R 5097	33µF	50V	63V	125	5	2	11	0.50	0.35	0.25
R 5104	47µF	25V	32V	115	5	2	11	0.50	0.35	0.25
R 5107	47µF	50V	63V	165	6.3	2.5	11	0.50	0.35	0.25
R 5108	47µF	63V	79V	190	8	3.5	11.5	0.50	0.35	0.25
R 5125	100µF	35V	44V	240	8	3.5	11.5	0.70	0.55	0.35
R 5127	100µF	50V	63V	260	8	3.5	11.5	0.75	0.60	0.40
R 5144	220µF	25V	32V	320	8	3.5	11.5	0.70	0.55	0.35
R 5147	220µF	50V	63V	455	10	5	12.5	0.95	0.70	0.50
R 5148	220µF	63V	79V	490	10	5	16	1.10	0.80	0.55
R 5153	330µF	25V	32V	440	8	3.5	11.5	0.75	0.60	0.40
R 5157	330µF	50V	63V	585	10	5	16	1.10	0.80	0.55
R 5158	330µF	63V	79V	710	10	5	20	1.10	0.90	0.60
R 5163	470µF	16V	20V	440	8	3.5	11.5	0.70	0.55	0.35
R 5167	470µF	50V	63V	755	10	5	20	1.50	1.15	0.70
R 5168	470µF	63V	79V	1050	16	7.5	25	1.70	1.40	0.80
R 5187	1000µF	50V	63V	1530	16	7.5	25	1.85	1.45	0.90
R 5214	3300µF	25V	32V	1975	16	7.5	25	2.25	1.80	1.05
R 5217	3300µF	50V	63V	2500	18	7.5	35.5	5.40	4.25	2.55
R 5222	4700µF	16V	20V	2260	16	7.5	31.5	1.85	1.45	0.90
R 5224	4700µF	25V	32V	2520	16	7.5	31.5	3.15	2.45	1.50
R 5228	4700µF	63V	79V	3560	25	12.5	50	6.80	5.65	4.25
R 5234	10000µF	25V	32V	3440	22	10	40	6.30	5.20	3.80

Lelon® PCB Mount Electrolytic Capacitors With “Snap In” Terminals (85°C Rated)



- Snap-in PCB mount type.
- 400V DC models are used primarily in power supply designs.
- Tolerance ±20%
- Temperature range -40° to +85°C.
- Rated life 2000hrs.
- **All quantities are supplied loose.**



Price Each	Value	Volts DC	Ripple (mA)	Dimensions	Pitch	RRP	10+	25+
R 5368	100µF	400V	710	220 x 30H	10	5.20	4.50	4.00
R 5428	330µF	400V	1460	250 x 50H	10	11.50	10.95	8.00
R 5448	470µF	400V	1990	300 x 50H	10	14.95	13.75	10.50
R 5465	680µF	200V	2300	300 x 30H	10	9.15	7.95	6.80
R 5541	3300µF	50V	2380	250 x 25H	10	6.30	6.00	4.45
R 5563	4700µF	100V	5130	300 x 50H	10	11.50	10.95	8.00
R 5573	5600µF	100V	5750	350 x 45H	10	13.25	12.25	10.50
R 5581	6800µF	50V	3850	300 x 35H	10	7.50	6.85	5.70
R 5590	8200µF	16V	2560	220 x 25H	10	6.30	6.00	4.45
R 5601	10000µF	50V	5020	300 x 40H	10	8.00	7.25	6.45

Motor Start Capacitors

- Low dissipation factor
- High insulation resistance
- -40°C to 85°C operating temperature
- Tolerance 5%
- Ideal for single phase induction motors.



Price Each	Value	Volts (AC)	Type	Dimensions	RRP	5+	10+
R 5610A	6µF	400V	Can	400 x 55H	19.50	13.50	11.50
R 5613A	20µF	400V	Can	450 x 75H	19.50	13.50	11.50
R 5616A	30µF	400V	Can	500 x 75H	19.50	13.50	11.50
R 5618	40µF	400V	Can	400 x 115H	19.50	13.50	11.50
R 5621	12µF	400V	Block	48L x 40W x 28D	19.50	13.50	11.50

Important Note For Wholesale Customers

All prices listed in this catalogue are RRP “retail” prices. To access our competitive wholesale pricing scheme apply for an account via www.altronics.com.au or phone the wholesale division in your state - see back cover for phone numbers.

Save with a VIP-Trade Card.

If you are in the trade and regularly purchase electronic goods for business purposes, chances are you will qualify for our Trade Discount. This entitles you to substantial discounts off our regular direct import prices. Actual discounts depend on the product type and quantity purchased. Typical discounts range between 20% to 30%. **Apply online.**